

SECTION 1 - SPECIFICATIONS

Gradeability

All Models - 25%

Inside Turning Radius

1932E2 - 0.5 m

2032E2/2632E2 - 1m

2646E2 - 1 m

3246E2 - 1.1 m

Lift (No Load in Platform)

1932E2

Up - 27 seconds

Down -26 seconds

2032E2

Up - 27-35 seconds

Down - 28-35 seconds

2632E2

Up - 34-42 seconds

Down - 39-47 seconds

2646E2

Up - 40-48 seconds

Down - 37-45 seconds

3246E2

Up - 56-64 seconds

Down - 45-55 seconds

Platform Capacity

1932E2 - 230 kg

2032E2 - 340 kg

2632E2 - 230 kg

2646E2 - 340 kg

3246E2 - 320 kg

Manual Platform Extension Capacity

All Models - 120 kg, - 1 person

Machine Weight

1932E2 - approx. 1360 kg

2032E2 - approx. 2091 kg

2632E2 - approx. 2415 kg

2646E2 - approx. 2086 kg

3246E2 - approx. 2812 kg

Wheelbase

1932E2 -1.3 m

2032E2/2632E2/2646E2/3246E2 - 1.7 m

Platform Height (Elevated)

1932E2 - 5.8 m

2032E2 - 6.1 m

2632E2/2646E2 - 7.9 m

3246E2 - 9.75 m

Platform Height (Stowed)

1932E2 - 1.0 m

2032E2 - 1.0 m

2646E2/3246E2 - 1.2 m

Machine Height (Stowed)

Standard Handrails

1932E2 - 2.0 m

2032E2 - 2.0 m

2632E2 - 1.2 m

2646E2 - 1.8 m

3246E2 - 2.3 m

Machine Length

1932E2 - 1.7 m

2032E2/2632E2/2646E2/3246E2 - 2.3 m

Machine Width

1932E2 - 0.8 m

2032E2 - 0.8 m

2646E2/3246E2 -1.2 m